

Longa Vertical 50 | 100 | 150 | 190

design: 2023, Cezary Zadorożny



Model	Longa Vertical
Material	Aluminium Concrete PMMA White Opal
Finish	Aluminium, coloured concrete
Dimensions	Ø 8 cm, L: 53 cm 103 cm 153 cm 193 cm
Power cord	Steel power cables with transparent sheath
Power supply	LED driver – external
Light Source	LED module 30W 60W 90W 120W LED, dimmable
Ceiling rose	Dedicated concrete ceiling rose
Weight	-

User Manual:

- Gently remove the packaging.
- Before starting the installation, check if the product is complete and contains all elements without any damage.
- Check if all cables have undamaged insulation of wires and conductors.
- If any damage occurred during transport, report it to the seller.
- Turn off the power in the room where the lamp will be installed. Switch off the circuit breakers or the main power switch.
- It is recommended that the fixture be installed by an electrician or a properly trained person.
- The manufacturer does not provide wall plugs with the lamp. It is recommended to purchase plugs specifically designed for the mounting surface.
- Use only recommended bulbs to avoid overheating.
- It is recommended to install with gloves.

Maintenance Tips:

- Use a soft, dry, or slightly damp cloth to wipe off dust.
- Do not use any aggressive cleaning agents, as this may cause permanent stains or discoloration of the lamp.
- Keep the user manual.



Longa Vertical 50 | 100 | 150 | 190

design: 2023, Cezary Zadorożny

Model	Longa Vertical
EAN code Longa Vertical 50	5902730888185
EAN code Longa Vertical 100	5902730888178
EAN code Longa Vertical 150	5902730888161
EAN code Longa Vertical 190	59027308887829
Producer	LOFTLIGHT Bottonova Sp. z o. o.
Design	Cezary Zadorożny
Type	Pendant lamp
Materials	Aluminium Concrete PMMA White Opal
Finish	Coloured concrete, aluminium
Diameter	8 cm
Length	53 103 153 193 cm
Power cord	Steel power cables with transparent sheath
Standard cord length	150 cm
Standard steel cables length	120 cm
Power supply	LED driver – external, 220-240V
Light source	LED module 30W 60W 90W 120W LED, dimmable
Light colour	3000K/4000K
Ceiling rose	Dedicated concrete ceiling rose
Number of light points	1
Weight	-
IP protection degree	IP20

